

5566-DongFang

R-5566 is a rutile titanium dioxide pigment with alumina, Zirconia and organic surface treatment, with high whiteness and gloss, high scattering power, high durability and excellent dispersibility.

RECOMMENDED APPLICATIONS

- Interior & Exterior paint
- Emulsion paint
- Powder coating
- Plastic and masterbatch
- Paper
- Rubber
- Inks

TYPICAL PROPERTIES

PARAMETER	VALUE	TEST METHOD
TiO ₂ content	≥ 93%	-
Rutile Content	≥ 97%	-
Inorganic Surface Treatment	Alumina, Zirconia	-
Organic Treatment	Yes	-
Particle Size	0.3 μm	-
Density	4.0	-
pH Value	6.5~8.5	-
Oil Absorption	18~23	-

*Measured within 48 hours of production

Safety

Good industrial hygiene practice should be used, generation of dust should be avoided. Please refer to the Safety Data Sheet for more information about how this product should be handled.

Storage

This product should not be stored outside or exposed to temperature extremes or to moisture. To ensure optimum performance, it is recommended that the product is used on a first in, first out basis from receipt of shipment.

Food Contact

Customers should seek confirmation of compliance with specific regulations by contacting LB Group.

Packaging

LB Group titanium dioxide pigments are available in 25kg bags and a range of flexible intermediate bulk containers.



www.chinookchem.com
info@chinookchem.com
+971 505 231023
+1 587 2884377



www.apamehr.com
info@apamehr.com
+98 21 22531747
+98 910 6002286